


## T521B106M035ATE100

T521, Tantalum, Polymer Tantalum, Commercial Grade, 10 uF, 20%, 35 VDC, SMD, Polymer, Molded, Low ESR, Non-Combustible, 100 mOhms, 2 mm, 1411 / 3528



Click [here](#) for the 3D model.

### General Information

|                          |  |
|--------------------------|--|
| Series                   | T521   |
| Dielectric               | Polymer Tantalum                               |
| Style                    | SMD Chip                                       |
| Description              | SMD, Polymer, Molded, Low ESR, Non-Combustible |
| Features                 | Low ESR, High Voltage                          |
| RoHS                     | Yes  |
| Termination              | Tin  |
| Typical Component Weight | 94.85 mg                                       |
| Shelf Life               | 52 Weeks                                       |
| MSL                      | 3  |

### Specifications

|                    |  |
|--------------------|--|
| Capacitance        | 10 uF  |
| Tolerance          | 20%  |
| Voltage DC         | 35 VDC (105C), 23.45 VDC (125C)  |
| Temperature Range  | -55/+125°C   |
| Rated Temperature  | 105°C  |
| Life               | 1000 Hrs (125C)  |
| Humidity           | 60C, 90% RH, 500 Hours, No Load  |
| Dissipation Factor | 8% 120Hz 25C   |
| Failure Rate       | N/A  |
| ESR                | 100 mOhms (100kHz 25C)   |
| Ripple Current     | 1410 mA (rms, 100kHz 45/85C), 987 mA (rms, 105C), 352.5 mA (rms, 125C) |
| Leakage Current    | 35 uA (5min 25°C)  |

### Dimensions

|   |                    |
|---|--------------------|
| L | 3.5mm +/-0.2mm     |
| W | 2.8mm +/-0.2mm     |
| H | 1.9mm +/-0.1mm     |
| T | 0.13mm REF         |
| S | 0.8mm +/-0.3mm     |
| F | 2.2mm +/-0.1mm     |
| A | 1.9mm MIN          |
| B | 0.4mm +/-0.15mm    |
| P | 0.5mm REF          |
| R | 1mm REF            |
| X | 0.1mm +/-0.1mm REF |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 178mm |
| Packaging Quantity | 2000       |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.