

# Power Inductor



## BMRB Series



### Overview

BMRx series is designed for low profile type with low RDC and ultra large current.  
Its molded magnetic shielded type is suitable for high-density mounting and ultra low buzz noise.  
Soldering conditions can be easily confirmed when mounting onto the board.  
This series also provides customers with embossed carrier type packaging for automatic mounting machine.

### Benefits

1. High rated current
2. Ultra low buzz noise

### Applications

1. DC-DC converters
2. Switchs and servers
3. DC-DC converters, inverters, and battery management systems.
4. Base stations, 5G infrastructure
5. Consumer Electronics: Smartphones, laptops, tablets, wearable devices, and gaming consoles.

### Product Information


| Series | L (mm) | W(mm) | T (mm) | Inductance (μH) |
|--------|--------|-------|--------|-----------------|
| BMRB   | 4.1    | 4.6   | 1.2    | 0.1 ~ 15        |
|        | 5.4    | 5.7   | 1.2    |                 |
|        | 5.2    | 5.4   | 1.2    |                 |
|        | 5.4    | 5.7   | 1.5    |                 |
|        | 5.4    | 5.7   | 1.8    |                 |
|        | 5.2    | 5.4   | 1.6    |                 |
|        | 6.6    | 7.3   | 1.2    |                 |
|        | 6.6    | 7.3   | 1.3    |                 |
|        | 6.6    | 7.3   | 1.6    |                 |
|        | 6.6    | 7.3   | 2.4    |                 |
|        | 6.6    | 7.3   | 3.0    |                 |
|        | 6.6    | 7.3   | 5.0    |                 |
|        | 6.6    | 7.3   | 5.0    |                 |



## BMRB00060612 Series Specification

**1 Scope** This specification applies to large current and low loss SMD power inductor.

**2 Part numbering**




**3 Temperature rating**

Operating Temperature: -55°C to 125°C.

Storage Temperature: (on tape & reel): -20°C to +40°C; 75% RH max.

**4 Marking**




Marking : 1R0

**5 Standard testing condition**

|             | Unless otherwise specified       | In case of doubt |
|-------------|----------------------------------|------------------|
| Temperature | Ordinary Temperature(15 to 35°C) | 20 to 30°C       |
| Humidity    | Ordinary Humidity(25 to 85% RH)  | 50 to 80 %RH     |

## BMRB00060612 Series Specification

### 6 Configuration and dimensions



Dimensions in mm

| Type | 060612          |
|------|-----------------|
| A    | $6.6 \pm 0.2$   |
| B    | $6.95 \pm 0.35$ |
| C    | 1.2 Max         |
| D    | $3.0 \pm 0.3$   |
| F    | $1.6 \pm 0.5$   |

| Size Code | Net weight(grms) |
|-----------|------------------|
| 060612    | 0.28(typ.)       |

### 7 Electrical characteristics


| Part number        | Inductance (uH) | Tolerance (±%) | Test Freq.  | I <sub>rms</sub> (A) Typ. | I <sub>sat</sub> (A) Typ. | RDC (mΩ) Max.(Typ.) | Marking |
|--------------------|-----------------|----------------|-------------|---------------------------|---------------------------|---------------------|---------|
| BMRB000606124R7MA1 | 4.7             | 20             | 100kHz,0.5V | 2.5                       | 3.5                       | 122(107)            | 4R7     |
| BMRB000606126R8MA1 | 6.8             | 20             | 100kHz,0.5V | 2.2                       | 2.8                       | 210(185)            | 6R8     |

#### Note:

- Operating temperature range -55°C to 125°C.
- I<sub>sat</sub> for Inductance drop 30% from its value without current.
- I<sub>rms</sub> for a 40°C temperature rise from 25°C ambient.
- The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions. Circuit design 125°C under worst case operating conditions. Component placement, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
- Absolute maximum voltage 30V DC. (Based on test method, it may not the same under different application, it is recommended to verify first.)

## BMRB00060612 Series Specification

### 8 BMRB00060612 Series 8.1 Construction



### 8.2 Material List

| Item | Part          | Description           |
|------|---------------|-----------------------|
| 1    | Magnetic core | Magnetic metal powder |
| 2    | Coil          | Enameled copper wire  |
| 3    | Terminals     | Copper based terminal |

## BMRB00060612 Series Specification

### 9 Reliability test items

#### 1-1.Mechanical Performance


| No    | Item                         | Specification                                                           | Test Method                                                                                                                                                               |
|-------|------------------------------|-------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1-1-1 | Vibration                    | Appearance: No damage<br>Inductance: within $\pm 10\%$ of initial value | Test device shall be soldered on the substrate<br>Oscillation Frequency: 10 to 55 to 10Hz for 1min<br>Amplitude: 1.5mm<br>Time: 2hrs for each axis (X, Y & Z), total 6hrs |
| 1-1-2 | Resistance to Soldering Heat | Appearance: No damage                                                   | Pre-heating: 150°C, 1min<br>Solder Composition: Sn/Ag3.0/Cu0.5<br>Solder Temperature: 260 $\pm 5$ °C<br>Immersion Time: 10 $\pm 1$ sec                                    |
| 1-1-3 | Solder ability               | The electrodes shall be at least 95% covered with new solder coating    | Pre-heating: 150°C, 1min<br>Solder Composition: Sn/Ag3.0/Cu0.5<br>Solder Temperature: 245 $\pm 5$ °C<br>Immersion Time: 4 $\pm 1$ sec                                     |
| 1-1-4 | Resistance to solvent        | There must be no change in appearance or obliteration of marking.       | Inductors must withstand 6 minutes of alcohol or water.                                                                                                                   |

#### 1-2.Environmental Performance

| No    | Item                | Specification                                                                                                                                                                                                 | Test Method                                                                                                                                                                                                                                                              |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
|-------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------------------|------------|---|-------|----|---|------|---|---|-------|----|---|------|---|
| 1-2-1 | Temperature Shock   | Appearance: No damage<br>Inductance:within±10% of initial value                                                                                                                                               | 10 cycles (Air to Air) 1 cycles shall consist of:<br>30 minutes exposure to -55°C<br>30 minutes exposure to 125°C<br>15 seconds maximum transition between temperatures                                                                                                  |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 1-2-2 | Temperature Cycle   |                                                                                                                                                                                                               | One cycle: <table><tr><th>Step</th><th>Temperature (°C)</th><th>Time (min)</th></tr><tr><td>1</td><td>-55±3</td><td>30</td></tr><tr><td>2</td><td>25±2</td><td>3</td></tr><tr><td>3</td><td>125±3</td><td>30</td></tr><tr><td>4</td><td>25±2</td><td>3</td></tr></table> | Step | Temperature (°C) | Time (min) | 1 | -55±3 | 30 | 2 | 25±2 | 3 | 3 | 125±3 | 30 | 4 | 25±2 | 3 |
| Step  | Temperature (°C)    |                                                                                                                                                                                                               | Time (min)                                                                                                                                                                                                                                                               |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 1     | -55±3               |                                                                                                                                                                                                               | 30                                                                                                                                                                                                                                                                       |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 2     | 25±2                |                                                                                                                                                                                                               | 3                                                                                                                                                                                                                                                                        |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 3     | 125±3               | 30                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                          |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 4     | 25±2                | 3                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                          |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 1-2-3 | Humidity Resistance | Total: 100cycles<br>Measured after exposure in the room condition for 24hrs<br>Temperature: 40±2°C<br>Relative Humidity: 90 ~ 95%<br>Time: 1000hrs<br>Measured after exposure in the room condition for 24hrs |                                                                                                                                                                                                                                                                          |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 1-2-4 | Heat Life           | Temperature: 85±3°C<br>Relative Humidity: 20%<br>Applied Current: Rated Current<br>Time: 1000hrs<br>Measured after exposure in the room condition for 24hrs                                                   |                                                                                                                                                                                                                                                                          |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |
| 1-2-5 | Cold Resistance     | Temperature: -55±3°C<br>Relative Humidity: 0%<br>Time: 1000hrs<br>Measured after exposure in the room condition for 24hrs                                                                                     |                                                                                                                                                                                                                                                                          |      |                  |            |   |       |    |   |      |   |   |       |    |   |      |   |

## BMRB00060612 Series Specification

### 10 Recommended IR reflow profile



Lead-Free(LF)

Refer to J-STD-020F

| Item        | Ramp-up      | Pre-heating   | Reflow     | Peak Temp. | Cooling              |
|-------------|--------------|---------------|------------|------------|----------------------|
| Temp. scope | R.T. ~150 °C | 150 °C~200 °C | 217 °C     | 260±5 °C   | Peak Temp.<br>150 °C |
| Time spec   | -            | 60~120 sec    | 60~150 sec | 20~40 sec  | -                    |

Note:


1. IR reflow times: within 3 times.
2. Nitrogen adopted is recommended while in IR reflow.

## BMRB00060612 Series Specification

### 11 Packaging

#### 11.1 Packaging-cover tape


The force for tearing off cover tape is 10 to 130 grams.



#### 11.2 Packaging quantity

| Type   | pcs/reel |
|--------|----------|
| 060612 | 1000     |

#### 11.3 Reel dimensions




Dimensions in mm

| Type   | A   | B   | C  | D  |
|--------|-----|-----|----|----|
| 060612 | 330 | 100 | 13 | 16 |

## BMRB00060612 Series Specification


### 11 Packaging

#### 11.4 Tape dimensions in mm



| Type   | $A_0$ | $B_0$ | $K_0$ | $D$ | $E$  | $W$ | $P$ | $P_0$ | $P_2$ |
|--------|-------|-------|-------|-----|------|-----|-----|-------|-------|
| 060612 | 6.9   | 7.6   | 1.5   | 1.5 | 1.75 | 16  | 12  | 4     | 2     |

### 12 Recommended pattern



Dimensions in mm

| Type   | A   | B   | C   |
|--------|-----|-----|-----|
| 060612 | 3.5 | 3.7 | 8.4 |

### 13 Note

1. Please make sure that your product has been evaluated and confirmed against your specifications when our product is mounted to your product.
2. Don't design/ mount any components in contact with this product.
3. The moisture sensitivity level (MSL) of products is classified as level 1.
4. Shelf life: 1 years from the date of shipment.

## BMRB00060612 Series Specification

### 14 Graph

