


DC-DC Converter (Isolation 1.5kVdc and 3kVdc) 3W to 6W SIP

BEA3/BEA6/CEA3/DKB3- series



a YAGEO company



- Ⓢ Input Voltage Range: 9-16V, 9-36V, 18-36V and 18-75V
- Ⓢ Output Voltage Range: 5V to 48V, Single and Dual (+/-Vout)
- Ⓢ Power Level: 3W to 6W
- Ⓢ Isolation: 1.5kVdc and 3kVdc
- Ⓢ Efficiency : up to 88% , no heatsinks required
- Ⓢ Operating Temperature Range: -40°C to +105°C
- Ⓢ Additional Features:
 - Ⓢ IEC/EN 62368-1 Approved
 - Ⓢ Low Ripple and Noise,
 - Ⓢ Output Short Circuit protection
 - Ⓢ Remote On/Off control, Thermal Shut-Down

Electrical Specification @ 25°C (For CEA3 3kVdc Isolation Op: -40°C to +85°C)

Model Number	Input Voltage Range(V)	Output Voltage (V)	Output Current (mA)		Input Current (mA)		Eff . (%)	Capacitive Load, max. (uF)
			Min. Load	Full Load	No Load	Full Load		
CEA3-12S1H3	9~18 Nominal: 12	5	100	600	30	305	82	2200

Electrical Specification @ 25°C (For BEA3 1.6kVdc Isolation Op: -40°C to +105°C)

Model Number	Input Voltage Range(V)	Output Voltage (V)	Output Current (mA)	Input Current (mA)		Eff . (%)	Capacitive Load, max. (uF)
			Full Load	No Load	Full Load		
BEA3-24S1W	9-36 Nominal: 24	5	600	20	151	83	3300
BEA3-24S2W		12	250	20	149	84	1000
BEA3-24D1W		±5	±300	20	154	81	±1000
BEA3-24D2W		±12	±125	20	152	82	±220
BEA3-24D3W		±15	±100	20	152	82	±150

Electrical Specification @ 25°C (For DKB3 3kVdc Isolation Op: -40°C to +105°C)

Model Number	Input Voltage Range(V)	Output Voltage (V)	Output Current (mA)	Input Current (mA) Typ.		Eff . (%) Typ.	Capacitive Load, max. (uF)
			Full Load	No Load	Full Load		
DKB3-05S1PH3	4.5-5.5 Nominal:5	5	600	10	750	80	470
DKB3-12S2PH3	10.8-13.2 Nominal:12	12	250	5	284	88	220

Electrical Specification @ 25°C (For BEA6 1.6kVdc Isolation Op: -40°C to +100°C)


Model Number	Input Voltage Range(V)	Output Voltage (V)	Output Current (mA)	Input Current (mA)		Eff . (%)	Capacitive Load, max. (uF)
			Full Load	No Load	Full Load		
BEA6-24S1W	9-36 Nominal: 24	5	1200	35	298	84	1100
BEA6-48S1W	18-75 Nominal: 48	5	1200	20	147	85	1100

Process and Materials

- Storage Temperature: -55°C to +125°C
- Compliance to J-STD:
 - A. J-STD-002: Solderability of Dipping at 255-260°C
 - B. J-STD-020: Moisture Sensitive Level 1
- All parts are packaged in tubes - see page 4 for details
- For full electrical characteristics, curves and applications, please refer to the detailed specification sheets available on request
- Lead Frame: Cooper Alloy
 - Underplated: Half Hard Ductile Nickel 40-118" (1.0-3.0um)
 - Over plated: 100% Tin electro-deposited per 240-400u"Min(6-10um)
 - Finish: Matte finish 100% Tin solder

Mechanical


CEA3H3



CEA3-XXXXH3		
PIN	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
3	Ve	Ve
4	No Pin	No Pin
5	NC	NC
6	+Vout	+Vout
7	-Vout	Common
8	Cext	-Vout

Unit: mm (inch for reference only)
Pin Section tolerances +/-0.1
General tolerances +/-0.5



BEA3W / BEA6W



BEA3/6-XXXXW		
PIN	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
3	Remote On/Off	
4	No Pin	No Pin
5	NC	NC
6	+Vout	+Vout
7	-Vout	Common
8	NC	-Vout

Unit: mm (inch for reference only)
Pin Section tolerances +/-0.1
General tolerances +/-0.5


DKB3H3



DKB3-XXXXPH3	
PIN	Single
1	+Vin
2	-Vin
5	-Vout
7	+Vout

Unit: mm (inch for reference only)
 Pin Section tolerances +/-0.1
 General tolerances +/-0.5

Wave Soldering Temperature Curve





DC-DC Converter (Isolation 1.5kVdc and 3kVdc) 3W to 6W SIP


BEA3/BEA6/CEA3/DKB3- series

Carton Package

CEA3H3/BEA3W/BEA6



INNER CARTON:567*135*125





EXPORT CARTON:598*287*150

TUBE=23PCS


INNER CARTON=45 TUBE=1035PCS

EXPORT CARTON=2 INNER CARTON=2*1035=2070PCS

DKB3PH



INNER CARTON:567*135*125



EXPORT CARTON:598*287*150

TUBE=25PCS

INNER CARTON=50 TUBE=50*25=1250PCS

EXPORT CARTON=2 INNER CARTON=2*1250=2500PCS

For More Information:

Americas - prodinfo_network_americas@yageo.com | Europe - prodinfo_network_emea@yageo.com | Asia - prodinfo_network_asia@yageo.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. Pulse Electronics, Inc. All rights reserved.